

RECOGNIZING TRIVIAL LINKS IN POLYNOMIAL TIME

CHAD MUSICK

ABSTRACT. Trivial links are unique up to number of link components, but they can be hard to recognize from arbitrary diagrams. We define a new measure of the complexity of a link embedding, the crumple, and show how this may be used to measure progress toward a trivial embedding. In conjunction with a modified form of arc presentations of links, we obtain a strictly monotonic, deterministic algorithm that recognizes triviality in links within polynomial time and space.

1. INTRODUCTION

A classical problem in knot theory asks whether or not a given link is trivial. Trivial links are unique up to number of link components, but they can be hard to recognize from arbitrary diagrams. A complementary problem asks how quickly triviality may be determined as a function of the number of crossings of a given diagram. We define a new measure of the complexity of a link embedding, the crumple, and show how this may be used to measure progress toward a trivial embedding. In conjunction with a modified form of arc presentations of links, we obtain a strictly monotonic, deterministic algorithm that recognizes triviality in links within polynomial time and space.

Theorem 1 answers both of these questions.

Theorem 1. *Given an arbitrary link diagram D with n crossings, the algorithm *ISTRIVIAL* determines in time and space polynomial in n whether or not D is a diagram of a trivial link.*

Key to the algorithm and its proof is the fact (due to Seifert [7]) that every link is the boundary of some properly embedded surface, and specifically that trivial links are the boundary of a family of disjoint, properly-embedded discs. We will show that for trivial links these discs may be viewed as being the composition of a number of smaller discs and that we can choose an embedding with a minimal number of these discs such that at least one of them will have a single part of its boundary on the boundary of the link and lie entirely on once of a set of concentric spheres. This disc can then be removed by a movement of a portion of the boundary of the link (equivalently by the movement of the equator of that sphere), yielding a new link embedding with fewer necessary discs. Both the existence of this composition and the ability to recognize it will be shown inductively.

The algorithm works by beginning with an encoded diagram (see section 2 for the encoding scheme) and prioritizing a reduction in complexity as measured by the following measures, listed in order of decreasing importance:

- (1) Length of the encoding sentence

- (2) Number of disjoint pieces of the link not lying on concentric spheres
- (3) Total length of the portion of the boundary not lying on concentric spheres
- (4) Number of *restrictive crossings* (Definition 2.10)
- (5) Number of crossings

The encoded diagram corresponds to an embedding that is contained in concentric spheres and rays from the common center. Using this embedding, at each step we allow a limited set of moves and require that the sequence be strictly monotonic, in lexicographic order, on the tuple of items $((1), (2), (3), (4), (5))$.

The moves all arise from the same source: compatible isotopies on the spheres in which portions of the boundary lie. These moves take the form of combinatorial rules for the encoding word. Visually, these may be seen as movement by the portions of the boundary lying on spheres and changes in the assignment of these portions to spheres.

We show that if the encoded link is trivial, one of these moves will produce a better encoding, and so by induction we can obtain the best possible encoding. For trivial links, this encoding yields the trivial diagram. For purposes of clarity, the algorithm is broken down into several sub-algorithms. Each of these requires only a sentence encoding a diagram.

Of course, this algorithm is inspired and made possible by prior work on the problem of link recognition, which we discuss now.

Cromwell [2] and Birman and Menasco [1] give a type of embedding, the *arc presentation*, of links that we have modified for our purposes. Although it is not presented as such in these papers, an arc presentation may be viewed as an embedding partitioned into two sets of pieces: semi-circles, each lying in a distinct sphere with ends on a plane common to the entire set and containing the center of the spheres, and ray segments between the ends of these semicircles. Our embedding differs from this in that we allow multiple semi-circles to occupy the same sphere so long as their intersection only occurs at the ends. An arc presentation may be encoded by means of a pair of permutations. We adopt a variant of this in our encoding scheme in order to allow for the greater flexibility in embeddings permitted by relaxation of the requirement that spheres be distinct.

Dynnikov [3] uses arc presentations to give an algorithm to recognize trivial links. This algorithm is polynomial in space but may require exponential time because there is no marker of progress toward a reduction in the encoding complexity. Although we adopt a different method of proof, the knowledge of Dynnikov's algorithm has motivated this work and influenced its shape. In particular, using a particular type of embedding to contain space complexity comes from study of Dynnikov's work.

Kauffman and Lambropoulou [4] develop a measure of the difficulty of diagrams of trivial links and clarify what it is that makes it hard to recognize triviality from classical diagrams. Figure 1.2 from their work is used extensively as an example in our work, and a study of the moves necessary to resolve their hard trivial links was helpful in development of this algorithm.

An earlier version of this paper used a trivial knot embedding due to Ochiai [6] to demonstrate the algorithm. Although this does not appear in the paper, the author continues to use this embedding in talks and to test ideas about the algorithm.

The author is grateful to Lars Hesselholt and Tomomi Kawamura for helpful feedback on exposition and early drafts. Conversations with Alexander Coward,

Louis H. Kauffman, and Akio Kawauchi have been helpful in clarifying areas that need changes and further explanation, and the author is grateful for these conversations.

2. DEFINITIONS AND NOTATION

2.1. Embeddings. Although we will begin with a link diagram, in the course of our proof we will proceed immediately to a family of embeddings of the same type as the link that produces the diagram. It is helpful to explain what this embedding looks like. We imagine the diagram as being the radial projection of a link onto the surface of a ball of radius 1. From this conception, we lift pieces of the diagram back to successively larger concentric spheres – each with an integer radius – such that the embedding is partitioned into two sets of pieces: those that lie in some sphere, which we will call *trails*, and those that are segments of rays proceeding from the common center of the spheres, which we will call *risers*. We will call a link embedded in this way a *tar link*.

Definition 2.1 (trail, origin of a trail). A *trail* is a closed, continuous curve of finite length lying in a sphere of integer radius. The *origin* of a trail is the center of the sphere in which it is contained.

Definition 2.2 (riser). A *riser* is a closed continuous line segment of integer length.

Definition 2.3 (link, link component, knot). A *link* with k components is the image of a function $L : S^1 \times \{1, 2, \dots, k\} \hookrightarrow S^3$. Each copy of S^1 is oriented. The image of L restricted to $S^1 \times \{i\}$ is the i th *component* of the link. A *knot* is a link with only one component.

Definition 2.4 (tar link). A *tar link*, or *trails-and-risers link*, is a link that is the union of a finite set of disjoint trails and disjoint risers with all trails having the same origin.

Remark. We note that all tar links are tame.

Definition 2.5 (link diagram). A *link diagram* is the radial projection of a link in general position onto the surface of the ball of radius 1. At each double-point, the portion further from the surface is said to cross over.

Definition 2.6 (tar link diagram, riser mark). A *tar link diagram* is the radial projection of a tar link with its trails in general position onto the surface of the ball of radius 1 whose center is the origin shared by the trails. The projection of each riser is marked by a dot, the *riser mark*. At each double-point, the trail lying in the sphere of greater radius is said to cross over.

Remark. Every tar link diagram is a link diagram partitioned by some additional dots.

A short example may make be helpful in understanding. Figure 2.1, an unknot diagram from a paper by Kauffman and Lambropoulou [4], has been partitioned into 12 pieces as follows. Six of these pieces are trails; each is marked with the radius of the sphere in which it lies and there is a partial order $\prec$ induced by the crossings. The other six pieces are risers; each is marked with a dot and runs between the spheres that contain the trails to either side of the riser mark. Every link diagram may be partitioned in this way. An initial marking placement of one riser mark between each pair of crossings is always sufficient.




FIGURE 2.1. A partitioned copy of Figure 1.2 from Kauffman and Lambropoulou [4]

2.2. Diagram encoding. Once we have chosen a particular partition of a link diagram, we obtain a tar link diagram that gives rise to a family of tar embeddings as described in the previous subsection. These differ by the heights assigned to the different trails. To encode this family, we will make a choice of an equator on each of the spheres of one of the tar embeddings. By choosing equators that are identical under the radial projection, we can easily read a descriptive sentence from a diagram in the following manner.

Definition 2.7 (binding circle). A *binding circle* of a tar link diagram is a counter-clockwise oriented closed loop that contains all of the riser marks and has only transverse crossings with the tar link diagram.

Draw a counter-clockwise oriented circle, called the *binding circle*, on the tar link diagram such that every riser mark is on the circle and every intersection between the diagram and the binding circle is transverse. We then uniquely label each riser mark. We choose an orientation on the link if one is not already given.

In order to construct the sentence, we first construct a word for each trail. Each word begins with either a + or a - depending on whether it first proceeds out of (+) or into (-) the binding circle. The second letter of each word is the label of the riser mark at which the trail begins. After this, for each time that the trail crosses the binding circle we list, in traversal order around the component of the link in which the trail is contained, the label of the riser mark that lies closest in a clockwise direction around the binding circle to the intersection between the original link diagram and the binding circle. Finally, the label of the riser mark at the terminal end of the trail is listed.

Definition 2.8 (topologically sorted). Given an ordered list of the elements in a partial order $\prec$, the list is *topologically sorted* if for every pair of comparable elements A and B , if B is listed before A then $A \prec B$.

A sentence is then formed by listing the words of all of the trails in a topologically sorted order where for trails A and B we write $A < B$ if B crosses over A . After all of the words are listed, we add a semicolon (;) and then write down the labels of the riser marks encountered as we proceed counter-clockwise around the binding circle from an arbitrary starting point until each has been written once. So long as no riser mark is labeled with $+$, $-$, or $;$, this sentence may be both encoded and decoded unambiguously. We will prove this latter claim. The link obtained by decoding such a sentence is unique up to equivalence class, but there may be differences between the obtained diagrams. We will show later that these differences do not change the equivalence class of the link and that, in fact, choosing the diagram with the least number of crossings from among the possible diagrams is straightforward.

Figure 2.2 shows an encoding of the same diagram as Figure 2.1 with a binding circle (drawn as a dotted line) and orientation chosen. It may be understood as follows. The word $-dae$ is listed first because the trail de crosses above all other trails. Because de first proceeds into the interior of the binding circle, its word begins with $-d$. Next, it crosses the binding circle, so we look clockwise around the circle and encounter the riser mark labeled a first, expanding the word to $-da$. Finally, the trail terminates at riser mark e , so the complete word is $-dae$. The next two words are those corresponding to trails fa and bc . Because these two are incomparable, we can choose the order between these two words arbitrarily. After the six words corresponding to trails are written, we write a $;$ to mark the beginning of the binding circle. Starting at a , we write down the labels of the riser marks as they are encountered around the binding circle in counter-clockwise order. The choice of a as the first letter of the binding circle is arbitrary. Because order around the binding circle is cyclic, any point on the binding circle is a suitable starting point.




FIGURE 2.2. An encoded diagram and the induced partial order

Definition 2.9 (Hasse diagram). A *Hasse diagram* is the representation of a partial order $\prec$ by a graph such that all edges point down and for every pair of elements A and B , there is an edge from B to A if and only if $A \prec B$.

The encoding of a link diagram captures the entirety of the relevant information for re-creating and manipulating the diagram. However, when using the ISTRIVIAL algorithm it is helpful to explicitly represent the partial order induced by the crossings. For this purpose, we use Hasse diagrams. The right-hand side of Figure 2.2 shows the Hasse diagram induced by the diagram on the left-hand side. Each node is labeled by the label of its initial riser mark followed by the label of its terminal riser mark.

Definition 2.10 (restrictive crossing). A *restrictive crossing* is a crossing between two trails A and B whose intersection appears on the Hasse diagram that represents the partial order among the trails.

2.3. Equivalent links and composition. We use the standard definition of link equivalence.

Definition 2.11 (ambient isotopy). An *ambient isotopy* between two links, L_0 and L_1 , is a continuous mapping $\Phi : S^3 \times [0, 1] \rightarrow S^3$ such that

$$\Phi(L_0, 0) = L_0, \quad \Phi(L_0, 1) = L_1$$

and every $\Phi_t : S^3 \rightarrow S^3$ given by $\Phi_t(X) = \Phi(X, t)$ is a homeomorphism of S^3 .

Definition 2.12 (equivalent links). Two links are *equivalent* if an ambient isotopy exists between them.

We are concerned exclusively with trivial links, so we provide a formal definition.

Definition 2.13 (trivial link). A link is trivial if it is a set of circles, each contained on the surface of distinct concentric spheres or if it is equivalent to such a link.

In the proof of the correctness of the ISTRIVIAL algorithm, we use a decomposition of the link into other links. We give the standard definition of composition of links.

Definition 2.14 (composition of links). Given two oriented links L_1 and L_2 contained in disjoint balls, their composition $L_1 \# L_2$ is the link that results from choosing a simple 4-sided 2-cell of which 1 edge belongs to L_1 , 1 edge belongs to L_2 , and both the remaining 2 edges and the face are empty, and replacing the edges with their complements in a way that keeps the same 0-cells as the start of the directed edges.

Figure 2.3 shows link composition. The composition of two oriented links is well defined. We refer the reader to any standard text, such as Murasugi [5] for the details. In our proof, we use the fact that composition does not turn a trivial link into a non-trivial link. This follows immediately from the fact that links form a semi-group under composition with the trivial link of one component acting as identity.

2.4. Complexity measures. In the introduction we indicated that we will use a tuple to measure the complexity of a tar link diagram. Some of these have been previously defined. We define the remaining measures here.




FIGURE 2.3. Composition of links

Definition 2.15 (length of a sentence). Let L_S be the sentence of a link. The *length* of the sentence is the number of letters used, including the letters $+$, $-$, and $;$, and counting each occurrence of a letter separately.

Definition 2.16 (crumple). Let L_S be the sentence of a link. The *crumple* of L_S is the minimum of the total Euclidean length of the risers from among all embeddings described by L_S .

As an example, the crumple of Figure 2.2 is 14, with contributions as follows: a contributes 3, b contributes 3, c contributes 1, d contributes 2, e contributes 3, and f contributes 2. It is not possible to improve upon this for that sentence.

Remark. The best possible crumple for any link is twice its bridge index, counting the bridge index of trivial components as 0 rather than the standard 1.

2.5. Sentence decoding. We have assumed without explanation that the sentence of a tar link may be decoded in a straightforward and unambiguous manner. We now show how this occurs.

First, we draw a circle. On this circle, we mark each of the riser marks, as listed in the sentence after the semicolon letter ($;$), counter-clockwise around the circle in the order listed. We then proceed word-by-word through the words of the trails, beginning at the first word and continuing. We may recognize the individual words because each begins with either $+$ or $-$, and these characters cannot occur at any other position in a word. For each word, we draw the trail described by the word in a way that avoids crossing any extant trail whenever possible between passing across the binding circle.

After every word is drawn if we desire to produce exactly the same embedding each time then we may do so in the following way. We start at 0 and number with consecutive integers the intersections between the diagram and the binding circle, beginning at the first riser mark listed in the binding circle portion of the sentence and proceeding counter-clockwise. From this, we obtain k numbers and two perfect matchings of the set of integers from 0 to $k - 1$: one corresponding to the interior of the binding circle and the other to the outside of the binding circle. We will call these matchings *in* and *out* respectively.

We space the integers 0 through k evenly around the intersection of the unit sphere and the xy plane with 0 lying at $(1, 0, 0)$, connect each pair of *in* by a chord, and then lift these to the upper half of the unit sphere such that their x and y coordinates do not change. We then do the same for each pair of *out*, except that these are lifted to the lower half of the unit sphere instead. After this, we radially project the trails out to spheres of integer radii that are compatible with the partial order induced by the crossing. It is guaranteed that if there are m trails then the assignment of index $j = 1, 2, \dots, m$ to the words in their order of occurrence and a

subsequent assignment of a radius of $m + 1 - j$ to the corresponding trails will be compatible, but there may be other compatible assignments.

Definition 2.17 (normed tar link). A tar link constructed from its sentence in the manner described above is a *normed* tar link.

Remark. Although we have been assuming an alphabet with as many letters as we desire, any finite alphabet with at least 2 characters distinct from the punctuation (+, -, and ;) will suffice without modification if each riser label uses the same number of letters. We may recover this length by dividing the length of the binding circle description by the number of words, which may be found by counting the occurrences of + and - characters.

2.6. Named moves. We use three special types of ambient isotopy and one purely combinatorial move to explain the relationship between various equivalent links.

Definition 2.18 (height shift). If L_1 and L_2 are normed tar links with the same sentence, then an ambient isotopy from L_1 to L_2 is a *height shift*.

We may see that for any sentence that encodes a link, the family of normed tar links of that sentence all differ by a height shift.

Definition 2.19 (trail move, flip). If L_1 and L_2 are equivalent tar links whose sentences differ only on one word under some equivalent ordering of the words, then an ambient isotopy from L_1 to L_2 is a *trail move*. If the only difference between changed word in L_1 and L_2 is the sign of the word, then the move is a *flip*.

We allow a re-ordering of the words because a trail move may cause an additional crossing relationship between two trails. If we prefer to view a trail move topologically, we may see it as a homeomorphism of the sphere containing the affected trail under which only the interior of that trail is changed. Alternately, we may see a trail move as making an alternate selection of binding circle for the sphere containing the affected trail and then producing a new sentence from this choice.

Definition 2.20 (riser move). If L_1 and L_2 are equivalent tar links whose sentences differ by the movement of one letter on the word of their binding circle and the requisite changes on the words of the trails, then an ambient isotopy from L_1 to L_2 is a *riser move*.

We may view a riser move either combinatorially or topologically. Combinatorially, a riser move is an alternate choice of equator for the set of spheres in which the riser lies and the corresponding changes to the sentence. Topologically, a riser is an ambient isotopy of the riser from one point on the mutual equator to a different point. Because it is an ambient isotopy, it may carry some trails across the equator with it. In whichever way it is viewed, because the words of the trails depend on the binding order, some of them may change independently of any change in their embedding.

The last type of move is combinatorial in nature but may result in height shifts and trail moves.

Definition 2.21 (riser removal). If L is the sentence of a tar link diagram in which trails a and b with a common endpoint are incomparable under the partial order induced by the crossings, then re-writing the sentence to omit the riser represented by this common endpoint is a *riser removal*.

3. PROOF OF THEOREM 1

Lemma 3.1. *Every trivial tar link in which no components have crumple 0 is the composition of a finite number of trivial knots, each of which is embedded with crumple 2 and has a non-trivial portion of its boundary on the boundary of the link.*

Proof. Let L be an arbitrary trivial tar link with no components of crumple 0. We proceed by induction on half the crumple of L .

If L has crumple 2, then the desired conclusion is trivially true.

Suppose that for up to a crumple of $2n$ the desired conclusion is true. Suppose that L is a trivial link of crumple $2(n+1)$ with no components of crumple 0.

Because L is trivial, it has a set of spanning discs. We examine the set of trails at maximal radius. For each of these trails the attached risers necessarily proceed to a sphere of lower radius. If none of these pairs of risers are connected at this smaller radius by a portion of the spanning disc which lies in the sphere of lower radius, then it is impossible that none of the components of L have crumple 0, because the discs must have no edges below the maximal trails, which all lie in the same sphere. Therefore, L is trivially embedded. By contradiction, there is at least one disc that may be cut, leaving a link with one more component, of which at least one has crumple 2.

We will call this new disc D and the remaining portion of the modified link L' . Because L' has crumple $2(n-1)$, by induction we know that there is a decomposition of L' into discs of crumple 2. We may choose a spanning disc for D such that this disc does not pass through the newly created gap between D and L' . As a worst case, we may do so in the following way. We know that D has a spanning disc, because $L' \cup D$ is trivial. We also know that L' and D may be enclosed in spheres which touch only at the mutual boundary of L' and D . If the spanning disc of D passes through this sphere, then by Dehn's Lemma we may find a resolution such that this is not the case because the portion of the spanning disc of D which passes through it cannot belong to the boundary of D and the portion of the sphere passed through cannot belong to the boundary of L' .

It remains to show that the disc of the decomposition of L' to which we have attached D did not have the new boundary as its only portion of the boundary which is also on the boundary of L . Let us call this disc D' . If D' no longer has any non-trivial portion of its boundary on the boundary of L , then the only portion of the boundary of D' on the boundary of L is at two riser marks. However, if D' was created in the decomposition of L' in the manner described here, then it would contain at least two non-trivial riser segments. Therefore, these segments may still exist and so L may be composed from discs each of crumple 2 and having a non-trivial portion of its boundary on the boundary of L .

By induction, if L is a trivial tar link with no components of crumple 0, then we may find a composition of L from trivial knots each with crumple 2 and a non-trivial portion of its boundary on the boundary of L . $\square$

Lemma 3.2. *Every trivial tar link is the composition of a finite number of trivial knots, each of which is either a component of the link embedded with crumple 0 or is embedded with crumple 2, and each of these knots has a non-trivial portion of its boundary on the boundary of the link.*

Proof. This follows directly from Lemma 3.1. Let L be an arbitrary trivial tar link. By the previous lemma, we may construct the portion of L that is not components

with 0 crumple as the composition of trivial knots of crumple 2. We may then add the components having crumple 0, again by composition because L is trivial by assumption. $\square$

Lemma 3.3. *If L is a normed trivial tar link with no possible riser removals and no components which may be collapsed to a disjoint loop by a trail move then there is a pair (t, h) , where h is a height shift and t is a trail move, such that the crumple of the sentence of thL is lower than the crumple of the sentence of L .*

Proof. Let L be a normed trivial tar link with no possible riser removals.

From Lemma 3.2 we may view L as the composition of a set $\mathcal{K}$ of trivial knots, each of which has crumple 2 or is a link component of L and has crumple 0.

We choose interior-disjoint spanning discs for every element of $\mathcal{K}$. The union of these discs forms a set of properly-embedded spanning discs for L , the existence of which is given by Seifert [7]. We examine the intersection pattern of these discs with the concentric spheres in which the trails of L lie.

Let $\mathcal{R} \subset \mathcal{K}$ be the set of trivial knots which have only a single connected component belonging to the boundary of L . We choose a member of $\mathcal{R}$ arbitrarily and label it D_1 .

Case 1: For our first case, suppose that the spanning disc of D_1 does not intersect any spheres except for the two in which its trails lie. In this case, we may choose a height shift which moves every other trail to a different sphere in a manner which does not affect this property of D_1 . If a set of risers passed through the space between the two trails of D_1 then the disc must pass through a sphere besides the two in which the trails of D_1 lie. By assumption, this is not the case. If a trail passed through the space between the two trails of D_1 then it would lie between two spheres with radii that differ by 1. This cannot be the case. Therefore, we may make a trail move on D_1 which causes it to collapse to a line under radial projection. We choose the move which affects a trail that lies in L . This reflects a move on L , and the height shift which allowed this move is designated h , the move is t , and we have our desired conclusion because the disc D_1 may be eliminated and the crumple of the decomposed link is a linear function of the number of components in $\mathcal{K}$ that have crumple 2.

Case 2: Suppose, though, that the spanning disc of D_1 intersects some sphere other than the two in which its trails lie, and that it must do so under every possible height shift. It must be that some riser would pass through the spanning disc of D_1 if this disc did not intersect some other sphere and that this intersection would occur under every possible height shift. Because no riser removals exist, this riser must be connected to trails that lie both above and below some of D_1 , and at least one of these must lie on the interior of the spanning disc of D_1 and every possible spanning disc of D_1 which does not leave the two spheres in which the trails of D_1 lie. There may be more than one such trail and disc, but for at least one of them, the member of $\mathcal{K}$ containing this enveloped trail must belong to $\mathcal{R}$ as well. We call it D_2 . We proceed by induction to find a chain of such trails in a similar manner. Each of them must belong to a knot in $\mathcal{R}$. Because $\mathcal{R}$ has a finite number of elements, we must run out of trails to serve as obstructions, and the final element of our chain will be of the type considered in Case 1. By the assumption that there are no components which can be shrunk to a disjoint disc, the chain cannot terminate in a member of $\mathcal{R}$ with crumple 0.

Because we can always find a knot an embedding of the type in case 1, we can always find a trail move t which will collapse an element of $\mathcal{R}$ under some height shift h . Because the number of discs is directly related to the crumple of the diagram of L , the removal of this disc means that the diagram of thL has a crumple lower than that of the diagram of L . $\square$

We note that Lemma 3.3 gives us a direct method of determining whether or not a given link is trivial. The difficulty with this method is that the sequence of trail moves that will lower the crumple of a trivial link to 0 may also result in a set of trails that, during the process, twist around the risers. This twisting complicates the diagram, which we may see by noting that it increases the sentence length. Because the process of finding the trail moves relies on the number of crossings, this twisting can increase the time necessary for finding the trail moves. This means that the method may be unsuitable when a reasonable bound is desired. In order to control for this, we have already introduced the riser move. This move allows us to untwist the diagram. By managing the twisting and the crumple together, we can assure ourselves of a tractable embedding as well as a tractable number of moves.

Lemma 3.4. *If S is the minimal-length sentence of a trivial tar link diagram, then S may be reached from the empty sentence by a sequence of the following:*

- (1) *the addition of a loop as a pair of new words each with length 3,*
- (2) *the addition of a riser by splitting an existing trail*
- (3) *a trail move that increases the crumple without decreasing the sentence length, or*
- (4) *a trail move that increases the sentence length*

Proof. If we drop the requirement that type of move described by (3) not decrease the sentence length, then this follows immediately from Lemma 3.3. We may see this by trivializing S by a sequence of trail moves, riser removals, and component removals and then reversing the sequence.

To see that this lemma holds in full generality, we begin by assuming that it almost holds but may require a trail move that both increases the crumple and decreases the sentence length.

We proceed by induction on the minimal number of moves required to construct a sentence. For the empty sentence, we may construct it in 0 moves, and it is vacuously true that all of the moves are of the desired type. Suppose that all sentences constructible in n moves may be constructed without a length-decreasing trail move. Let S be a sentence that requires $n + 1$ moves to construct.

By assumption, the first n moves may be performed without any length-decreasing trail moves. We examine the final move. If this move must be a length-decreasing trail move, then it must be that it could not be made earlier because if it could then we could find a sentence, constructible in fewer moves, that requires a length-decreasing trail move. By the inductive assumption, this is not the case. Because it could not be made earlier, it must be that the move was not possible until after the remainder of the moves had been performed. From this, we know that the n th move must have added a riser mark. $\square$

The introduction of the requirement that S be a minimal-length sentence of a given tar link diagram means that we must find some way to achieve a shorter

sentence for the same diagram in those instances in which we have a diagram of a trivial tar link that is not a minimal-length sentence of that diagram. A naive method would be to search among all possible sentences of the diagram, but the solution to this would not, in general, be polynomial. We instead relax the condition that the diagram be the same one and instead require only that it be an equivalent one. This gives us a tractable method for finding a shorter sentence, should one exist because unnecessary length of the sentence is created by unnecessary twisting in the equators.

Lemma 3.5. *If S is the sentence of a trivial tar link with crumple more than 0, then one of the following will exist for S :*

- (1) *a riser that may be removed*
- (2) *a component that may be removed as trivial and disjoint*
- (3) *a trail move that will result in a shorter sentence,*
- (4) *a trail move that will result in a lower crumple without lengthening the sentence,*
- (5) *an equator which will reduce the number of restrictive crossings without increasing any of the previous measures*
- (6) *an equator which will reduce the number of crossings without increasing any of the previous measures*
- (7) *an equator which will cause one of the first 4 items to occur or to exist when applied to a subset of the spheres in which a link with the sentence S is embedded.*

Proof. Let S be the sentence of a tar link with the crumple of the diagram of S greater than 0.

If one of the cases (1), (2), (3), (4), occurs then there is nothing more to do. We assume that none of these occurs in S . However, we know that if S is actually the sentence of a trivial tar link then the only reason that one of these would not occur is that S is not the best possible minimal length sentence to describe the diagram given by S .

If the better diagram could be found solely by trail moves, then one of the other conditions would have occurred, so we know that we need at least one riser move. In order to find this, we choose each riser in turn and test its effect on the remaining risers. There are a finite number of places to which a riser could move – one for each space between crossings of the mutual equators – and each of these placements, occurring by means of a straight movement across one of the sets of concentric hemispheres. We view each such movement as dragging behind it any trail that could be shorter if that riser did not exist in its old position and pushing ahead of it every trail that must be longer if the riser is to exist in its new position. If no such movement of a riser results in an improved sentence, then this is the best sentence for the diagram given by S . However, this would be a contradiction of the previous Lemma, and so at least one riser move allows for a better sentence. This shows that the absence of cases (1), (2), (3), and (4) forces the presence of one of the remaining cases. $\square$

Theorem 1. *Given an arbitrary link diagram D with n crossings, the algorithm ISTRIVIAL determines in time and space polynomial in n whether or not D is a diagram of a trivial link.*

Proof. Let D be an arbitrary link diagram with n crossings. Let S be a tar link sentence of D . The length of S is linearly related to the number of crossings.

From Lemma 3.5, if S is trivial, then either there is a shorter sentence of an equivalent link or there is sentence that is better on one of the remaining metrics. ISTRIVIAL checks each of these in turn, replacing S with the resulting sentence if it finds an improvement.

If there is a riser that may be removed, REMRISER finds and removes it. Trivial components will be removed by either FLATTEN or SHORTEN. Trail moves that yield shorter sentences will be found by SHORTEN. Trail moves that lower the crumple or improve the crossings will be found by FLATTEN. Riser moves that improve the sentence will be found by MOVERISE.

Because all possible moves are found before ISTRIVIAL returns, it will correctly determine whether or not a link is trivial. Because each step is finite in length and the tuple (sentence length, number of risers, crumple, restrictive crossings, crossings) is decreasing in a strictly monotonic sequence, there can be at most $\mathcal{O}(n^8)$ moves – $\mathcal{O}(n)$ of these come from the sentence length, $\mathcal{O}(n)$ from the number of risers, and $\mathcal{O}(n^6)$ from the crumple and the crossing measures, each of which contributes $\mathcal{O}(n^2)$.

The time required for each of the sub-algorithms is as follows.

REMDUPS requires $\mathcal{O}(n)$ time to remove all double letters.

REMRISER requires a linear amount of time to check each riser, and there are a linear number of risers, so it requires $\mathcal{O}(n^2)$ time. The time required for the REMDUPS use in REMRISER is dominated by the other portions.

For each trail, FLATTEN requires a constant amount of time per crossing to check for a crumple-lowering isotopy. There are at worst $\mathcal{O}(n^2)$ crossings, and $\mathcal{O}(n)$ trails. It takes a linear amount of time to minimize obstructions, but this time is dominated by the time to check for isotopies, so FLATTEN requires time $\mathcal{O}(n^3)$.

For each trail, SHORTEN requires a linear amount of time to check for a length-reducing isotopy.

For each riser in MOVERISE, there are $\mathcal{O}(n)$ positions to which each riser may move, so there are $\mathcal{O}(n^2)$ checks required. Each of these checks needs the worst time of REMRISER, FLATTEN, and SHORTEN, so MOVERISE requires time $\mathcal{O}(n^5)$.

Because the longest portion of ISTRIVIAL needs time $\mathcal{O}(n^5)$ and there are $\mathcal{O}(n^8)$ steps, ISTRIVIAL runs in time no worse than $\mathcal{O}(n^{13})$ before considering the specific data and computational model. The space required for ISTRIVIAL is quadratic, because although the space required for a sentence is only linear, the crossings between trails must be stored as well. Although the actual time required will depend on the specific method chosen to compute portions of the algorithm, none of these methods requires worse than polynomial time or space, and so the entire algorithm is polynomial. $\square$

We remark that if desired, the space used for the ISTRIVIAL algorithm may be kept as linear, but that this comes at the expense of recalculating crossings and an increase in the time required for the algorithm.

Experimentally, the length of the sentence, the crumple, and the crossings tend to fall together, and so the running time tends to be small enough to do by hand for diagrams with no more than one hundred crossings.

4. ALGORITHMS

Algorithm 4.1 ISTRIVIAL

Require: A link diagram D
 $V \leftarrow$ a set of riser marks of D
 $S' \leftarrow$ a sentence of D with the riser marks V
repeat
 $S \leftarrow S'$
 $S' \leftarrow \text{SOFTIMP}(S')$
 $S' \leftarrow \text{MOVERISE}(S')$
until $S = S'$
if S is the empty sentence **then**
 return D is trivial
else
 return D is non-trivial
end if

Algorithm 4.2 SOFTIMP

Require: A tar link sentence S
 $S \leftarrow S'$
 $S' \leftarrow \text{REMRISER}(S')$
 $S' \leftarrow \text{FLATTEN}(S')$
 $S' \leftarrow \text{SHORTEN}(S')$
return S'

Algorithm 4.3 REMRISER

Require: A tar link sentence S

```

for all risers  $r$  in  $S$  do
   $r^+ \leftarrow$  the word of the trail which terminates at riser  $r$ 
   $r^- \leftarrow$  the word of the trail which begins at riser  $r$ 
  if the trails of  $r^+$  and  $r^-$  are incomparable then
     $S \leftarrow$  topological sort the words of  $S$  such that  $r^+r^-$  appears
    if the trails of  $r^+$  and  $r^-$  end and begin, respectively, in the same hemisphere
    then
      replace  $r^-$  with the word formed by removing the sign
    else
      replace  $r^-$  with the word formed by removing the sign and first letter
    end if
  for all occurrences of the letter  $r$  in the trail words of  $S$  do
    replace  $r$  by the letter preceding it in the binding order
  end for
  remove  $r$  from the binding word of  $S$ 
end if
end for
return REMDUPS( $S$ )

```

Algorithm 4.4 FLATTEN

Require: A tar link sentence S

```

for all trails  $t$  in  $S$  do
  choose a set of heights to minimize obstructions on the sphere of  $t$ 
  if there is an isotopy  $\sigma$  of  $t$  in its sphere to reduce crumple or improve crossings
  without increasing crumple then
     $S' \leftarrow$  the sentence of the chosen embedding modified by  $\sigma$ 
    if REMDUPS( $S'$ ) is not longer than  $S$  then
      return REMDUPS( $S'$ )
    end if
  end if
end for
return  $S$ 

```

Algorithm 4.5 SHORTEN

Require: A tar link sentence S

```

for all trails  $t$  in  $S$  do
  choose a set of heights to minimize obstructions on the sphere of  $t$ 
  if there is an isotopy  $\sigma$  of  $t$  such that  $t$  crosses the equator fewer times then
     $S' \leftarrow$  the sentence of the chosen embedding modified by  $\sigma$ 
    return REMDUPS( $S'$ )
  end if
end for

```

Algorithm 4.6 REMDUPS

Require: A tar link sentence S

$S' \leftarrow S$

repeat

$S \leftarrow S'$

if there is a pair of repeated letters xx in S' **then**

if xx are the first letters of the trail word **then**

 replace xx with x and switch sign of the word in S'

else if xx are the last letters of the trail word **then**

 replace xx with x in S'

else

 remove xx from S'

end if

end if

until $S' = S$

return S

Algorithm 4.7 MOVERISE

Require: A tar link sentence S

for all risers r in S **do**

for all positions p_r between equator crossings **do**

 push r to p_r , through the $+$ hemisphere

$S' \leftarrow$ the sentence of this new embedding

$S'' \leftarrow \text{SOFTIMP}(S')$

if $\text{BETTER}(S'', S')$ **then**

return S''

end if

 push r to p_r , through the $-$ hemisphere

$S' \leftarrow$ the sentence of this new embedding

$S'' \leftarrow \text{SOFTIMP}(S')$

if $\text{BETTER}(S'', S')$ **then**

return S''

end if

end for

end for

return S

Algorithm 4.8 BETTER

Require: Tar link sentences S and S'

```

if  $S$  is shorter than  $S'$  then
  return TRUE
else if  $S$  is longer than  $S'$  then
  return FALSE
end if
if  $S$  has fewer risers than  $S'$  then
  return TRUE
end if
if  $S$  has a lower crumple than  $S'$  then
  return TRUE
else if  $S'$  has a lower crumple than  $S$  then
  return FALSE
end if
if  $S$  has fewer restrictive crossings than  $S'$  then
  return TRUE
else if  $S'$  has fewer restrictive crossings than  $S$  then
  return FALSE
end if
if  $S$  has fewer crossings than  $S'$  then
  return TRUE
end if
return FALSE

```

5. AN EXAMPLE

We show here an example of the ISTRIVIAL algorithm, simplified for purposes of demonstration, working on the knot shown in Figure 2.2.

We have already chosen a set of riser marks and a sentence: we let S be $-\text{dae}-\text{fdbfa}+\text{bac}+\text{cafd}-\text{ebf}+\text{aabb};\text{aecbdf}$. We see from the corresponding Hasse diagram that no adjacent trails are incomparable, and so REMRISER simply runs REMDUPS. This changes the sentence to $-\text{dae}-\text{fdbfa}+\text{bac}+\text{cafd}-\text{ebf}-\text{ab};\text{aecbdf}$.

We now run FLATTEN. The left side of Figure 5.1 shows a projection of the spheres containing the trail ab and ef . We see that if we flip ab , it will no longer intersect anything on sphere ef and that this is an ordinary isotopy of ab within its sphere. We do so, and the result is shown in the center of Figure 5.1. The right-hand side of the same figure shows the resulting Hasse diagram. Our sentence S is now $-\text{dae}-\text{fdbfa}+\text{bac}+\text{cafd}-\text{ebf}+\text{ab};\text{aecbdf}$. There are no duplicates, and so REMDUPS has no effect.

We now run SHORTEN. We see immediately that the word $-\text{dae}$ may be shortened to either $-\text{de}$ or $+\text{de}$. We arbitrarily choose $-\text{de}$. We see after this that $-\text{fdbfa}$ may be shortened to $+\text{fba}$ and that $+\text{cafd}$ may be shortened to $+\text{cd}$ and $-\text{ebf}$ to $-\text{ef}$. Our resulting sentence is $-\text{de}+\text{fba}+\text{ab}+\text{bac}+\text{cd}-\text{ef};\text{aecbdf}$. Figure 5.2 shows a picture of this diagram and its corresponding Hasse diagram. Next, we examine potential riser moves. We see that we may move b to be adjacent to a through the $+$ hemisphere and shorten $+\text{bac}$ to $-\text{bc}$; as a result of the move, $+\text{fba}$ becomes $+\text{fca}$. The resulting sentence is $-\text{de}+\text{fca}+\text{ab}-\text{bc}+\text{cd}-\text{ef};\text{abecbdf}$. A diagram of this sentence and the corresponding Hasse diagram are shown in figure 5.3.

Because we changed the sentence during the first iteration, we start again with REMRISER. We may see from Figure 5.3 that we may remove both a and b without changing the chosen heights. This gives the sentence $-\text{de}+\text{fcffc}+\text{cd}-\text{ef};\text{ecdf}$. REMDUPS shortens this to $-\text{de}+\text{fc}+\text{cd}-\text{ef};\text{ecdf}$. This is a trivial diagram. No changes are made by the algorithm until a third iteration, when the remaining risers are removed, yielding the empty sentence and returning that the original diagram was of a trivial knot.




FIGURE 5.1. FLATTEN step in the algorithm




FIGURE 5.2. SHORTEN step in the algorithm




FIGURE 5.3. MOVERISE step in the algorithm

REFERENCES

- [1] J. Birman and W. Menasco. Special positions for essential tori in link complements. *Topology*, 33(3):525–556, 1994.
- [2] Peter R. Cromwell. Embedding knots and links in an open book I: Basic properties. *Topology Appl.*, 64(1):37–58, 1995.
- [3] Ivan Dynnikov. Arc-presentation of links. monotonic simplification. *Fund. Math.*, 190:29–76, 2006, math.GT/0208153.
- [4] Louis H. Kauffman and Sofia Lambropoulou. Unknots and molecular biology. *Milan J. Math.*, 74:227–263, 2006, math.GT/0601525.
- [5] Kunio Murasugi. *Knot Theory & Its Applications*. Birkhäuser, 1996. English edition.
- [6] Mitsuyuki Ochiai. Non-trivial projections of the trivial knot. *Astérisque*, 192:7–10, 1987.
- [7] Herbert Seifert. Über das Geschlecht von Knoten. *Math. Ann.*, 110(1):571–592, 1935.